

SAFETY DATA SHEET

Creation Date 06-November-2009 Revision Date 13-May-2019 Revision Number 4

1. Identification

Product Name Petroleum ether, boiling range 40-60°C

Cat No. : AC326790000; AC326790010; AC326790025

CAS-No 64742-49-0 Synonyms Ligroine

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Importer/Distributor
Fisher Scientific
Acros Organics
Fisher Scientific
One Reagent Lane
Ottawa, ON K2E 7L6,
Canada

Manufacturer
Fisher Scientific
One Reagent Lane
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids

Skin Corrosion/irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 2

Category 2

Category 2

Category 2

Target Organs - Central nervous system (CNS).

Aspiration Toxicity Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes skin irritation

May cause drowsiness and dizziness



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Call a POISON CENTER/ doctor if you feel unwell

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposa

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS-No	Weight %			
Hydrocarbons, C6, isoalkanes < 5% n-hexane	64742-49-0	55-100			
(Iso-Hexane)					

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Inhalation Move to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance: give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration. Risk of serious damage to the lungs.

Ingestion Aspiration hazard. Do not induce vomiting. Call a physician or Poison Control Center

immediately. If vomiting occurs naturally, have victim lean forward.

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like Most important symptoms/effects

headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically Notes to Physician

Fire-fighting measures

CO₂, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire Suitable Extinguishing Media

with water spray.

Unsuitable Extinguishing Media Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

-33 °C / -27.4 °F **Flash Point**

Method -No information available

230 °C / 446 °F **Autoignition Temperature**

Explosion Limits

Upper No data available Lower No data available Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Avoid contact with skin,

eyes and clothing. Take precautionary measures against static discharges.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment. Up

7. Handling and storage

Handling

Wear personal protective equipment. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Do not ingest. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts

of the equipment must be grounded.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat

and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Viton (R)	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid Appearance Colorless

OdorPetroleum distillatesOdor ThresholdNo information availablepHNo information available

Melting Point/Range No data available

Boiling Point/Range 48 - 70 °C / 118.4 - 158 °F

Flash Point -33 °C / -27.4 °F
Evaporation Rate 13 (Butyl acetate = 1.0)

Flammability (solid,gas) Not applicable

Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor Pressure250 hPa @ 250 °CVapor Density>1 @ 101 kPa

Specific Gravity 0.65

SolubilityInsoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature230 °C / 446 °FDecomposition TemperatureNo information available

Viscosity 0.45 mm2/s at 25 °C (ASTM D445)

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component LD50 Oral Hydrocarbons, C6, isoalkanes < 5% LD50 > 5000 mg/kg (Rat)		LD50 Dermal	LC50 Inhalation		
Hydrocarbons, C6, isoalkanes < 5%	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h		
n-hexane (Iso-Hexane)					

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 Irritating to eyes and skin

 Sensitization
 No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Hydrocarbons, C6,	64742-49-0	Not listed				
isoalkanes < 5%						
n-hexane (Iso-Hexane)						

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard Category 1

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting

No information available **Endocrine Disruptor Information**

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Hydrocarbons, C6,	Not listed	Not listed	Not listed	LC50: = 2.6 mg/L, 96h
isoalkanes < 5% n-hexane				(Chaetogammarus marinus)
(Iso-Hexane)				

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Will likely be mobile in the environment due to its volatility. **Mobility**

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN1208 **UN-No HEXANES Proper Shipping Name**

Hazard Class 3 **Packing Group** Ш

TDG

UN-No UN1208 **Proper Shipping Name HEXANES**

Hazard Class Packing Group Ш

IATA

UN-No UN1208 **HEXANES Proper Shipping Name**

Hazard Class 3 Ш **Packing Group**

IMDG/IMO

UN-No UN1208 **HEXANES Proper Shipping Name**

Hazard Class 3 Packing Group II

15. Regulatory information

International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Hydrocarbons, C6, isoalkanes <	Х	-	Х	265-151-9	-		Х	-	Х	Х	KE-2562
5% n-hexane (Iso-Hexane)											3

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 06-November-2009

 Revision Date
 13-May-2019

 Print Date
 13-May-2019

Revision Summary

This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS