sigma-aldrich.com

SAFETY DATA SHEET

Version 5.7 Revision Date 12/10/2015 Print Date 02/07/2016

1. PRODUCT AND COMPANY IDENTIFICATION

| 1.1 | Product identifiers Product name | : | Toluene |
|-----|--------------------------------------|---|---|
| | Product Number Brand Index-No. | : | 244511 Sigma-Aldrich 601-021-00-3 |
| | CAS-No. | : | 108-88-3 |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

| Company | : | Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA |
|------------------|---|--|
| Telephone Fax | | +1 800-325-5832 +1 800-325-5052 |

1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure (Category 2), H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



| Signal word | Danger |
|---------------------|--|
| Hazard statement(s) | |
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H401 | Toxic to aquatic life. |
| Aldrich 044544 | |

| Precautionary statement(s) | |
|----------------------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and |
| | understood. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. |
| P264 | Wash skin thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face |
| | protection. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/ |
| | physician. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. |
| | Rinse skin with water/shower. |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for |
| | breathing. Call a POISON CENTER or doctor/ physician if you feel |
| | unwell. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P331 | Do NOT induce vomiting. |
| P332 + P313 | If skin irritation occurs: Get medical advice/ attention. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to |
| | extinguish. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

| Formula | : | C ₇ H ₈ |
|---------------------|---|-------------------------------|
| Molecular weight | : | 92.14 g/mol |
| CAS-No. | : | 108-88-3 |
| EC-No. | : | 203-625-9 |
| Index-No. | : | 601-021-00-3 |
| Registration number | : | 01-2119471310-51-XXXX |

Hazardous components

| Component | Classification | Concentration |
|-----------|--|---------------|
| Toluene | | |
| | Flam. Liq. 2; Skin Irrit. 2; 2; STOT SE 3; STOT RE Asp. Tox. 1; Aquatic Acut H225, H304, H315, H336 H361, H373, H401 | 2; e 2; |

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | Value | Control parameters | Basis |
|-----------|----------|--|----------------------|--|
| Toluene | 108-88-3 | TWA | 100 ppm 375 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | STEL | 150 ppm 560 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | TWA | 200 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 |
| | Remarks | Z37.12-196 | 7 | |
| | | CEIL | 300 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 |
| | | Z37.12-196 | 7 | |
| | | Peak | 500 ppm | USA. Occupational Exposure Limits (OSHA) - Table Z-2 |
| | | Z37.12-196 | 7 | |
| | | TWA | 20 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | Visual impairment Female reproductive Pregnancy loss 2015 Adoption Substances for which there is a Biological Exposure (see BEI® section) Not classifiable as a human carcinogen | | c |
| | | TWA | 100 ppm 375 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| | | ST | 150 ppm 560 mg/m3 | USA. NIOSH Recommended Exposure Limits |

Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-----------|----------|------------------|----------------|-----------------------|---|
| Toluene | 108-88-3 | Toluene | 0.0200 mg/l | In blood | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | Prior to last sh | ift of workwe | ek | |
| | | Toluene | 0.0300 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | | End of shift (As | s soon as po | ssible after exposure | e ceases) |
| | | o-Cresol | 0.3000 mg/g | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | | End of shift (As | s soon as po | ssible after exposure | ceases) |

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| a) | Appearance | Form: liquid Colour: colourless |
|----|---|---------------------------------------|
| b) | Odour | aromatic |
| c) | Odour Threshold | No data available |
| d) | рН | No data available |
| e) | Melting point/freezing point | Melting point/range: -93 °C (-135 °F) |
| f) | Initial boiling point and boiling range | 110 - 111 °C (230 - 232 °F) |

| g) | Flash point | 4.0 °C (39.2 °F) - closed cup |
|-----|--|--|
| h) | Evaporation rate | No data available |
| i) | Flammability (solid, gas) | No data available |
| j) | Upper/lower flammability or explosive limits | Upper explosion limit: 7 %(V) Lower explosion limit: 1.2 %(V) |
| k) | Vapour pressure | 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F) |
| I) | Vapour density | No data available |
| m) | Relative density | 0.865 g/mL at 25 °C (77 °F) |
| n) | Water solubility | 0.5 g/l at 15 °C (59 °F) |
| o) | Partition coefficient: n- octanol/water | No data available |
| p) | Auto-ignition temperature | 535.0 °C (995.0 °F) |
| q) | Decomposition temperature | No data available |
| r) | Viscosity | No data available |
| s) | Explosive properties | No data available |
| t) | Oxidizing properties | No data available |
| Oth | ner safety information | |

9.2 Other safety information No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity No data available

10.2 Chemical stability Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5** Incompatible materials Strong oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - > 5,580 mg/kg

LC50 Inhalation - Rat - 4 h - 12,500 - 28,800 mg/m3

LD50 Dermal - Rabbit - 12,196 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit Result: Skin irritation - 24 h

Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation No data available

Germ cell mutagenicity

Rat Liver DNA damage

Carcinogenicity

- IARC: 3 Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Damage to fetus possible Suspected human reproductive toxicant

Reproductive toxicity - Rat - Inhalation Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Developmental Toxicity - Rat - Oral Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information

RTECS: XS5250000

Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals., Central nervous system

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

| Toxicity to fish | LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h | | |
|---|--|--|--|
| | NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d | | |
| Toxicity to daphnia and other aquatic invertebrates | EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h | | |
| | Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h | | |
| Toxicity to algae | EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h | | |
| | EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h | | |

12.2 Persistence and degradability

Biodegradability Result: - Readily biodegradable

12.3 **Bioaccumulative potential**

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d - 0.05 mg/l

Bioconcentration factor (BCF): 90

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

.

| REGULATORY INFORMATION | | | | | |
|--|-----------------------|-------------------|------------------|--|--|
| IATA UN number: 1294 Proper shipping name | Class: 3 : Toluene | Packing group: II | | | |
| IMDG UN number: 1294 Proper shipping name | Class: 3 : TOLUENE | Packing group: II | EMS-No: F-E, S-D | | |
| Poison Inhalation Haza | ard: No | | | | |
| DOT (US) UN number: 1294 Proper shipping name Reportable Quantity (F | | Packing group: II | | | |
| DOT (US) | | | | | |

15. F

SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

| The following components are subject to reporting levels esta | blished by SARA Title | III, Section 313: |
|---|-----------------------|-------------------|
| | CAS-No. | Revision Date |
| Toluene | 108-88-3 | 2007-07-01 |
| SARA 311/312 Hazards | | |
| Fire Hazard, Acute Health Hazard, Chronic Health Hazard | | |

Massachusetts Right To Know Components

| Toluene | CAS-No. 108-88-3 | Revision Date 2007-07-01 |
|---------------------------------------|---------------------|--------------------------|
| Pennsylvania Right To Know Components | | |
| | CAS-No. | Revision Date |
| Toluene | 108-88-3 | 2007-07-01 |
| Sigma-Aldrich - 244511 | | |

| New Jersey Right To Know Components | | |
|--|----------|---------------|
| | CAS-No. | Revision Date |
| Toluene | 108-88-3 | 2007-07-01 |
| California Prop. 65 Components | | |
| WARNING: This product contains a chemical known to the | CAS-No. | Revision Date |
| State of California to cause birth defects or other reproductive | 108-88-3 | 2009-02-01 |
| harm. | | |
| Toluene | | |

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

| Aquatic Acute | Acute aquatic toxicity |
|---------------|--|
| Asp. Tox. | Aspiration hazard |
| Flam. Liq. | Flammable liquids |
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H401 | Toxic to aquatic life. |
| | |
| Repr. | Reproductive toxicity |
| Skin Irrit. | Skin irritation |

HMIS Rating

| Health hazard: | 2 |
|---|--------|
| Chronic Health Hazard: Flammability: | 3 |
| Physical Hazard | 0 |
| | |
| NFPA Rating | |
| NFPA Rating Health hazard: | 2 |
| • | 2 3 |

Further information

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.7

Revision Date: 12/10/2015

Print Date: 02/07/2016